



ENGLISH

COMPLETE





CHARACTERISTICS

Specifically designed for the requirements of small industry and laboratories.

- No operator's license required (Italy only)
- No periodic USL visits required (Italy only)
- Easy installation and maintenance
- Minimum overall dimensions
- Available with LP gas or diesel burners
- All-in-one with completely automatic control
- Finished in stainless steel sheet
- Atmospheric burner



ACCESSORIES

Every PG model boiler is equipped with the following standard accessories:

- Counterweight-type safety valve
- Ball valve for steam attachment
- Drain attachment with ball valve
- Sampling group with 2 bronze gauge cocks
- Water-level sight gauge with direct reading
- Pressure gauge and 3-way gauge cock with pressure test flange
- Centrifugal pump with check valves and connecting tubes
- Automatic water-level controller with stainless steel probes
- Manostat for generator pressure control
- Electronic safety probe for burner cut-off
- Electric panel complete with all electrical devices and connections.

OPTIONALS

PAL monobloc including water softener and stainless steel feed water tank

	PRESS	PRESS STEAM POWER CAPACITY liters			DIMENSIONS mm			WEIGHT	
MODEL	bar	Kg/h	Kcal/h	TOTAL	WORKING	L	W	Н	Kg
PG 30	4	30	19.000	72	43	540	700	1400	
PG 60	4,8	60	29.900	60	40	700	950	1670	
PG 90	3	90	57.000	80	54	700	950	1760	
PG 100	4,8	100	63.700	60	40	700	950	1760	
PG 150	4	150	95.300	70	50	700	950	1820	
PG 180		180							

